

# BLUSKY™ FLOWCAST 335

## Admixture specifically designed for dry cast concrete

### Description

**BLUSKY™ FLOWCAST 335** is an admixture specifically designed for dry cast concrete.

**BLUSKY™ FLOWCAST 335** allows optimization of the dosage of cement in order to obtain a specific class of resistance.

**BLUSKY™ FLOWCAST 335** increases mechanical strength.

**BLUSKY™ FLOWCAST 335** eases the placing of dry concrete.

### Indicative characteristics

Form	:	Pale Yellow Liquid
Specific Gravity	:	1.050 ± 0.02
pH	:	≥ 6

### Packaging

20 kg Bucket, 225 Kgs Barrel & bulk in 10 KL tanker

### Safety

- Wear hand gloves, safety shoes and safety goggles while using and handling the product.
- In case eyes or mouth are affected wash with plenty of clean water and seek medical treatment immediately

Before use, refer to the Material Safety Data Sheet. The MSDS is available on [www.bluskyscpl.com](http://www.bluskyscpl.com).

### Domains of application

- All cement types excluding white cement
- Machine manufactured and dry cast
- Precast

### Precautions

Protect from frost.  
Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.

### Method of use

Dosage: 0.1 to 1.50 kg for 100 kg of cement.  
This product is completely miscible in water.  
This product must be added to the mixing water before adding to the mixer.  
The optimum dosage of this product can only be established after trial tests, taking into account the rheological characteristics and the required mechanical performances of the concrete.

### Shelf Life

If stored in unopened containers at normal ambient temperatures, a shelf-life of approximately 12 months.

The information contained in this technical data sheet is given to the best of our knowledge and the results from extensive testing in order to remain as objective as possible. However, it cannot, in any case be considered as a warranty involving our liability in case of misuse or any different use of our products from the "Application" paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Consult the latest update of the technical data sheet on our website [www.bluskyscpl.com](http://www.bluskyscpl.com)